



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: EIGA110

Issue date: 16/01/2013 Revision date: 11/03/2024 Version: 1.9

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Substance
Name	: Sulphur hexafluoride
Trade name	: Sulfur hexafluoride 3.0; Sulfur hexafluoride 4.5; Sulfur hexafluoride 5.0
EC-No.	: 219-854-2
CAS-No.	: 2551-62-4
REACH registration No.	: 01-2119458769-17-0005
Product code	: 000010021723
Formula	: SF6

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Relevant identified uses	: Industrial use. Perform risk assessment prior to use. Test gas/Calibration gas. Chemical reaction / Synthesis. Laboratory use. Use for manufacture of electronic/photovoltaic components.
Use of the substance/mixture	: Formulation of mixtures with gas in pressure receptacles. Insulant. Use as an Intermediate (transported, on-site isolated). Using gas for metal treatment.

##### 1.2.2. Uses advised against

Uses advised against	: Do not inhale product on purpose because of the risk of asphyxiation. Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses.
----------------------	---

#### 1.3. Details of the supplier of the safety data sheet

Linde GmbH Division Gas  
Seitnerstr. 70  
DE- 82049 Pullach  
Germany  
T +49 8974460  
[info@linde.com](mailto:info@linde.com)

#### 1.4. Emergency telephone number

Emergency number	: UMCO/NCEC: +44 1865 407333 (English); +49 89 220 61012 (German)
------------------	---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Physical hazards      Gases under pressure : Liquefied gas      H280

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS04

Signal word (CLP)

: Warning

Hazard statements (CLP)

: H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage

: P403 - Store in a well-ventilated place.

Supplemental information

: Do not inhale product on purpose because of the risk of asphyxiation.  
Contains fluorinated greenhouse gases listed in Annex I of EU 517/2014 as amended.  
Asphyxiant in high concentrations.

### 2.3. Other hazards

Other hazards

: Asphyxiant in high concentrations. Contact with liquid may cause cold burns/frostbite. The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Sulphur hexafluoride	CAS-No.: 2551-62-4 EC-No.: 219-854-2 REACH-no: 01-2119458769-17-0005	100	Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

### 3.2. Mixtures

Not applicable



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
First-aid measures after skin contact	: In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes.
First-aid measures after ingestion	: Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.
---	---

#### 4.3. Indication of any immediate medical attention and special treatment needed

None.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.
Unsuitable extinguishing media	: Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire	: No reactivity hazard other than the effects described in sub-sections below.
Specific hazards	: Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	: Hydrogen fluoride. Sulphur dioxide.

#### 5.3. Advice for firefighters

Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures

: Act in accordance with local emergency plan. Try to stop release. Evacuate area. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.

##### 6.1.2. For emergency responders

Emergency procedures

: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Oxygen detectors should be used when asphyxiating gases may be released. See section 5.3 of the SDS for more information.

#### 6.2. Environmental precautions

Try to stop release.

#### 6.3. Methods and material for containment and cleaning up

Methods and material for containment and cleaning up : Ventilate area.

#### 6.4. Reference to other sections

See also sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into work area.



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Conditions for safe storage, including any incompatibilities

- : Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Sulphur hexafluoride (2551-62-4)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Schwefelhexafluorid
AGW (OEL TWA) [1]	30000 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	5000 ppm
Peak exposure limitation factor	8(II)



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sulphur hexafluoride (2551-62-4)	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

Sulphur hexafluoride (2551-62-4)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	6074 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	0.15 mg/l
PNEC aqua (marine water)	1.5 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Provide adequate general and local exhaust ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Consider the use of a work permit system e.g. for maintenance activities.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Wear goggles when transfilling or breaking transfer connections.

Standard EN 166 - Personal eye-protection - specifications

#### 8.2.2.2. Skin protection

##### Hand protection:

Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.

Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.

#### Other skin protection



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

### Other information:

Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.

Never use any kind of filtering respiratory protection equipment when working with this substance due to it having poor or no warning properties.

Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

None in addition to the above sections.

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	
Physical state	: Gas
Colour	: Colourless.
Form	: Liquefied gas
Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
Melting point	: -50.8 °C
Freezing point	: Not applicable
Boiling point	: -64 °C
Flammability	: Non flammable.
Oxidising properties	: No oxidising properties.
Explosive limits	: Not known.
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Viscosity, dynamic	: 0.016 mPa·s @ 25 °C; Experimental result, Supporting study; Not applicable for gases and gas mixtures.
Solubility in water	: 41 mg/l
Partition coefficient n-octanol/water (Log Kow)	: 1.68
Partition coefficient n-octanol/water (Log Pow)	: Not applicable for gas mixtures.
Vapour pressure	: 21 bar(a)
Vapour pressure at 50°C	: Not applicable.
Critical pressure	: 3760 kPa



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Density	: 1.39 g/cm <sup>3</sup> 20.0 °C
Relative density	: 1.4
Relative vapour density at 20°C	: Not applicable.
Relative gas density	: 5
Particle characteristics	: Not applicable Not applicable for gases and gas mixtures. Nanoforms are not relevant for gases and gas mixtures.

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Critical temperature	: 45.5 °C
----------------------	-----------

#### 9.2.2. Other safety characteristics

Molecular mass	: 146 g/mol
Gas group	: Compressed gas
Additional information	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Avoid moisture in installation systems.

### 10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: No known effects from this product. pH: Not applicable for gases and gas mixtures.





# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation	: No known effects from this product. pH: Not applicable for gases and gas mixtures.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Reproductive toxicity	: Not classified
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

### Sulphur hexafluoride (2551-62-4)

Viscosity, kinematic	Not applicable for gases and gas mixtures.
----------------------	--

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Other information : The substance/mixture has no endocrine disrupting properties.

## SECTION 12: Ecological information

### 12.1. Toxicity

Assessment	: Classification criteria are not met.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

### Sulphur hexafluoride (2551-62-4)

LC <sub>50</sub> 96 h - Fish [mg/l]	236 mg/l
EC <sub>50</sub> 48h - Daphnia magna [mg/l]	247 mg/l
EC <sub>50</sub> 72h - Algae [mg/l]	No data available.

### 12.2. Persistence and degradability

### Sulphur hexafluoride (2551-62-4)

Assessment	Not applicable for inorganic products.
------------	--

### 12.3. Bioaccumulative potential

### Sulphur hexafluoride (2551-62-4)

Partition coefficient n-octanol/water (Log Pow)	Not applicable for gas mixtures.
Partition coefficient n-octanol/water (Log Kow)	1.68



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.4. Mobility in soil

#### Sulphur hexafluoride (2551-62-4)

Assessment	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
------------	--

### 12.5. Results of PBT and vPvB assessment

Assessment	: Not classified as PBT or vPvB.
------------	----------------------------------

### 12.6. Endocrine disrupting properties

Other adverse effects	: No known effects from this product.
Assessment	: The substance/mixture has no endocrine disrupting properties.

### 12.7. Other adverse effects

Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: No effect on the ozone layer.
Global warming potential [CO <sub>2</sub> =1]	: 22800
Effect on global warming	: When discharged in large quantities may contribute to the greenhouse effect. Contains fluorinated greenhouse gases listed in Annex I of EU 517/2014 as amended. For quantities refer to cylinder label.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Refer to supplier's waste gas recovery programme. Contact supplier if guidance is required. Discharge to atmosphere in large quantities should be avoided. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <a href="http://www.eiga.eu">http://www.eiga.eu</a> for more guidance on suitable disposal methods. Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID






ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1080	UN 1080	UN 1080	UN 1080	UN 1080



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.2. UN proper shipping name</b>				
SULPHUR HEXAFLUORIDE	SULPHUR HEXAFLUORIDE	Sulphur hexafluoride	SULPHUR HEXAFLUORIDE	SULPHUR HEXAFLUORIDE
<b>Transport document description</b>				
UN 1080 SULPHUR HEXAFLUORIDE, 2.2, (C/E)	UN 1080 SULPHUR HEXAFLUORIDE, 2.2	UN 1080 Sulphur hexafluoride, 2.2	UN 1080 SULPHUR HEXAFLUORIDE, 2.2	UN 1080 SULPHUR HEXAFLUORIDE, 2.2
<b>14.3. Transport hazard class(es)</b>				
2.2	2.2	2.2	2.2	2.2
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment, Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure valve is closed and not leaking, - Ensure valve outlet cap nut or plug (where provided) is correctly fitted, - Ensure valve protection device (where provided) is correctly fitted.

#### Overland transport

Classification code (ADR) : 2A  
 Special provisions (ADR) : 392, 662  
 Limited quantities (ADR) : 120ml  
 Excepted quantities (ADR) : E1  
 Packing instructions (ADR) : P200  
 Mixed packing provisions (ADR) : MP9  
 Portable tank and bulk container instructions (ADR) : (M)  
 Tank code (ADR) : PxBN(M)  
 Tank special provisions (ADR) : TA4, TT9  
 Vehicle for tank carriage : AT  
 Transport category (ADR) : 3  
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV10, CV36  
 Hazard identification number (Kemler No.) : 20



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Orange plates



Tunnel restriction code (ADR)

: C/E

### Transport by sea

Limited quantities (IMDG)	: 120 ml
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P200
EmS-No. (Fire)	: F-C
EmS-No. (Spillage)	: S-V
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Liquefied, non-flammable, odourless gas. Much heavier than air (5.1).

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: FORBIDDEN
PCA limited quantity max net quantity (IATA)	: FORBIDDEN
PCA packing instructions (IATA)	: 200
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 200
CAO max net quantity (IATA)	: 150kg
ERG code (IATA)	: 2L

### Inland waterway transport

Classification code (ADN)	: 2A
Special provisions (ADN)	: 386, 392
Limited quantities (ADN)	: 120 ml
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: 2A
Special provisions (RID)	: 392, 662
Limited quantities (RID)	: 120ml
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P200
Mixed packing provisions (RID)	: MP9
Portable tank and bulk container instructions (RID)	: (M)
Tank codes for RID tanks (RID)	: PxBN(M)
Special provisions for RID tanks (RID)	: TA4, TT9, TM6
Transport category (RID)	: 3
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW10, CW36
Colis express (express parcels) (RID)	: CE3
Hazard identification number (RID)	: 20

### 14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : (EC) No 517/2014 : on fluorinated greenhouse gases and repealing Regulation (EC) No 842/2006.

##### REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

##### REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

##### POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

##### Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 1005/2009)

##### VOC Directive (2004/42)

Restrictions on use : Not allowed for magnesium die-casting. (Regulation (EU) No 517/2014).  
Not allowed to be used for inflating tyres. (Regulation 517/2014).

##### Seveso Directive (Disaster Risk Reduction)

Seveso Directive : 2012/18/EU (Seveso III) : Not covered.

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

##### 15.1.2. National regulations

Ensure all national/local regulations are observed.

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work

Directive 2016/425/EEC on personal protective equipment

Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX)

Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

##### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).  
Water hazard class (WGK) : WGK nwg, Non-hazardous to water (Classification according to AwSV; ID No. 846).  
Kenn-Nr. : 846  
Storage class (LGK, TRGS 510) : LGK 2A - Gases (except aerosol dispensers and lighters).



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 3, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 6.2, LGK 7, LGK 10.

Joint storage with restrictions permitted for

: LGK 2A, LGK 2B, LGK 5.1C, LGK 8A, LGK 11, LGK 10-13.

Joint storage permitted for

: LGK 8B, LGK 12, LGK 13.

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

### 15.2. Chemical safety assessment

A CSA has been carried out.

## SECTION 16: Other information

### Indication of changes:

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Indication of changes	
Changed item	Change Comments

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
	ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
	ATE - Acute Toxicity Estimate
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAO	Cargo Aircraft only / Cargo Aircraft only
CAS-No.	Chemical Abstract Service number
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
	CSA - Chemical Safety Assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC <sub>50</sub>	Median effective concentration
EC	European Inventory of Existing Commercial Chemical Substances
ED	Endocrine disrupting properties
	EINECS - European Inventory of Existing Commercial Chemical Substances



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC <sub>50</sub>	Median lethal concentration
LD <sub>50</sub>	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PCA	Passenger and Cargo Aircraft / Passenger and Cargo Aircraft
PNEC	Predicted No-Effect Concentration
	PPE - Personal Protection Equipment
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
	RMM - Risk Management Measures
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
STOT-RE	Specific Target Organ Toxicity-Repeated Exposure
STOT-SE	Specific Target Organ Toxicity-Single Exposure
UFI	Unique Formula Identifier
	UN - United Nations
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class



# Sulphur hexafluoride

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training. For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at <http://www.eiga.eu>.
- Other information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 16g : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu>.

Full text of H- and EUH-statements:	
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

- The classification complies with : ATP 12
- DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
- Details given in this document are believed to be correct at the time of going to press.
- Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Safety Data Sheet (SDS), EU DE

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

End of document